


BRUCHA panel WP-F

wall exposed fastened




fire protection


exterior PROFILE options - close-up



symbol image - WP-F profile 1



DETAIL/joint geometry



PANEL TYPE	WP-F 60	WP-F 80	WP-F 100	WP-F 120	WP-F 140	WP-F 150	WP-F 160	WP-F 180	WP-F 200	WP-F 240
core thickness mm	60	80	100	120	140	150	160	180	200	240
U-value W/m²K - EN 14509 incl. joint section	0.681	0.512	0.412	0.346	0.298	0.279	0.261	0.233	0.210	0.176
weight kg/m²	16.39	18.79	21.19	23.59	25.99	27.19	28.39	30.79	33.19	37.99
fire resistance*	EI 30	EI 90	EI 90	EI 180	EI 180	EI 180	EI 180	EI 180	EI 240	EI 240

*Certificates must be checked for the usage case in question (horizontal/vertical/span width etc.).

MANUFACTURING TOLERANCES

in line with EN 14509

SOUND INSULATION

32 dB (frequency dependent)

MANUFACTURING LENGTHS

max. 15.6 m (extra-long transport from 13.6 m) ATTENTION! Danger of kinking due to heavy weight in the case of long panels!

SPAN WIDTH TABLES

according SandStat. calculation

FIRE BEHAVIOR

in line with EN 13501-1, Euroclass A2s1d0, **non-combustible**

BRUCHA



fire protection

BRUCHA panel WP-F

wall exposed fastened

DESIGN AND SURFACES Standard - coil-coated, hot-dip galvanised steel sheet

EXTERIOR


- Exposed side 25 µm polyester coating with a PVC protective film (not UV-resistant - protect from direct sunlight).
The film must be removed before installation or immediately afterwards.
- profile 1 = Standard, for other profiles see WP-F PROFILE options
- metal gauge: 0.6 mm (smaller metal gauge on request)

INTERIOR

- Exposed side 25 µm polyester coating with a PVC protective film (not UV-resistant - protect from direct sunlight).
The film must be removed before installation or immediately afterwards.
- profile 1 = standard (profile 2 and 3 on request)
- metal gauge: 0.6 mm (smaller metal gauge on request)

INSULATION CORE

- structural, web-oriented mineral fibre wool
- securely attached to the sheet steel shell
- density approx. 120 kg/m³, 140 kg/m³ available on request



STANDARD COLORS

in accordance with BASIC color range

PANEL CONNECTION

Tongue and groove system in which the panels interlink precisely with no thermal bridge.

TENDER TEXT

download from: bruchacom

EXTERNAL MONITORING

National and international tests and quality standards. We will send the certificates on request.

VAPOUR DIFFUSION

Determined by climatic conditions inside building. Panels must be installed vapour tight.

PANEL INSTALLATION

When working with our products, please follow our installation guidelines at bruchacom/downloads



bruchacom

